Industrial Class Power Supply

Industrial Mini-Redundant AC Power Supply



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3 V	+5 V	+12 V	-5	-12 V	+5 Vsb			
APS-930XAR	300 W	18 A	25 A	16 A	0.5 A	0.5 A	2.0 A	ATX12	90-264AC full range	UL/CSA/TUV
APS-942XAR	420 W	25 A	35 A	28 A	0.5 A	1.2 A	2.0 A	EPS12	90-264AC full range	UL/CSA/TUV

■ Dimensions: 185 x 150 x 86 (mm)

Industrial Dual Redundant AC Power Supply



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb			
APS-6300F	300 W	25 A	20-36 A	17 A	0.8 A	0.8 A	2 A	ATX	Input voltage: 90-264AC full Range	UL/CSA/TUV
APS-6400F	400 W	25 A	36 A	17 A	0.8 A	0.8 A	2 A	ATX	manual switch, Frequency: 47 Hz-63 Hz	UL/CSA/TUV

■ Dimensions: 187 x 167 x 183 (mm)
■ Non RoHS series

Industrial AC Power Supply PS2 Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb			
APS-935XA-EPS12	350 W	25 A	35 A	22 A	0.8 A	1 A	2 A	EPS12	90-264VAC full range	UL/CSA/TUV
APS-940XA-ATX12	400 W	25 A	35 A	30 A	0.8 A	1 A	2 A	ATX12	90-240VAC full range	UL/CSA/TUV
APS-940XA-EPS12	400 W	25 A	35 A	30 A	0.8 A	1 A	2 A	EPS12	90-264VAC full range	UL/CSA/TUV
APS-946XA-EPS12	46 0W	30 A	40 A	32 A	0.8 A	1 A	2 A	EPS12	90-264VAC full range	UL/CSA/TUV

■ Dimensions: Standard PS2 form factor, 140 x 150 x 86 (mm)

Industrial DC-DC Power Supply PS2 Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	DC Voltage Input Range	Certificate
		+3.3	+5 V	+12 V	-5 V	-12 V	+5 Vsb			
APS-930XDC/48	300 W	15 A	23 A	8 A	1 A	3 A	1.2 A	ATX	-40--57VDC	UL/CUL/TUV

■ Dimensions: 150 x 140 x 86.2 (mm)

Industrial AC Power Supply 1U Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb			
APS-9125XU	250 W	14 A	25 A	12 A	--	1 A	1.5 A	ATX12	90-264AC full range	UL/CSA/TUV
APS-9130XU	300 W	20 A	24 A	20 A	0.5 A	0.5 A	1.5 A	ATX12	90-264AC full range	UL/CSA/TUV

■ Dimensions: 205 x 100 x 40.5 (mm)

Industrial Flex ATX AC Power Supply for 1U Chassis



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3 V	+5	+12 V	-5 V	-12 V	+5 Vsb			
APS-915FXM	150 W	10	14 A	4.2 A	--	0.3 A	2 A	ATX	90-264VAC	UL/CUL/TUV

■ Dimension: 150 x 81.5 x 40.6 (mm)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000