
cBP-3213PR

3U CompactPCI® 32-bit 13-slot Backplane with Rear I/O



cBP-3213PR



cBP-3213PR with cBP-R3213 Rear View

Specifications

Model Name	cBP-3213PR
PICMG®	2.0 R3.0, 2.1 R2.0, 2.11 R1.0
Dimensions	425.7 x 128.7 (mm, W x H)
Segment	1
cPCI Bus	32-bit/33 MHz
System Slot	Right-hand side
System Slot Rear I/O	P2 rear I/O with AB-type shroud
Peripheral Slot	12 slots (cBP-R3213 bridge board is required)
Peripheral Slot Rear I/O	P2 rear I/O with AB-type shroud
Bridge	cBP-R3213 rear bridge board, TI2050 P2P bridge
Power Socket	PICMG® 2.11 47-pin socket x 3 (for 3U 8HP power module)
V (I/O)	3.3 V or 5 V selectable, factory default is 5 V
Power Connectors	AC/DC input, ATX connector x 2, DC screw terminals
Other Connectors	INH#, Reset, PWR_FAL#, Voltage LEDs

Ordering Information

Model Number	Description/Configuration
cBP-3213PR	3U CompactPCI 32-bit 13-slot backplane with 3 PSU sockets and rear I/O
cBP-R3213	Removable rear bridge board

Note: cBP-R3213 is sold separately from cBP-3213PR.