Industrial Class Power Supply

Industrial Mini-Redundant AC Power Supply



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	AC Voltage Input Range	Certificate
APS-250RAXM	250W	14A	16A	9A	1A	1A	0.82A	ATX	90-132VAC or 190-260VAC, manual switch	UL/CSA/TUV
APS-930RAXA	300W	18A	25A	16A	0.5A	0.5A	2.0A	ATX12	90-264VAC full range	UL/CSA/TUV

■ Dimensions: 150 x 176 x 86 (mm)

Industrial Dual Redundant AC Power Supply



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	AC Voltage Input Range	Certificate
APS-6300F	300W	0-25A	20-36A	9-17A	0.8A	0.8A	20-36A	ATX	Input voltage: 90-132VAC or 190-260VAC,	UL/CSA/TUV
APS-6400F	400W	0-25A	20-36A	17A	0.8A	0.8A	20-36A	ATX	manual switch, Frequency: 47Hz-63Hz	UL/CSA/TUV

■ Dimensions: 167 x 189 x 190 (mm)

Industrial AC Power Supply PS/2 Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	AC Voltage Input Range	Certificate
APS-925XA-ATX12	250W	25A	25A	13A	0.3A	0.8A	2A	ATX12	100-240VAC full range	UL/CSA/TUV
APS-930XA-ATX12	300W	25A	35A	22A	0.8A	1A	2A	ATX12	90-240VAC full range	UL/CSA/TUV
APS-930XA-ST	300W	20A	25A	15A	0.5A	1A	2A	ATX12	90-264VAC full range	UL/CSA/TUV
APS-935XA-ATX12	350W	25A	35A	26A	0.8A	1A	2A	ATX12	90-240VAC full range	UL/CSA/TUV
APS-940XA-ATX12	400W	25A	35A	30A	0.8A	1A	2A	ATX12	90-240VAC full range	UL/CSA/TUV
APS-940XA-ST	400W	30A	40A	18A	0.5A	1A	2A	ATX12	90-264VAC full range	UL/CSA/TUV
APS-946XA-EPS12	460W	30A	40A	32A	0.8A	1A	2A	EPS12	90-264VAC full range	UL/CSA/TUV

■ Dimensions: Standard PS/2 form factor, 150 x 176 x 86 (mm)

Industrial DC-DC Power Supply PS/2 Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	DC Voltage Input Range	Certificate
APS-927/48	250W	--	25A	10A	1A	1A	--	AT	-40-57VDC	UL/CUL/TUV
APS-927/24	250W	15A	30A	15A	2A	2A	1.2A	ATX	19-32VDC	UL/CSA/TUV

■ Dimensions: 150 x 140 x 86.2 (mm)

Industrial AC Power Supply 1U Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	AC Voltage Input Range	Certificate
APS-9120XA-ST	200W	20A	25A	13A	0.5A	1A	2A	ATX12	90-264VAC full range	UL/CSA/TUV
APS-9130XA-ST	300W	20A	25A	18A	0.5A	1A	2A	ATX12	90-264VAC full range	UL/CSA/TUV

■ Dimensions: 205 x 100 x 40.5 (mm)

Industrial Open Frame AC Power Supply for 1U Chassis



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	AC Voltage Input Range	Certificate
APS-912XA	120W	12A	14A	6A	--	1A	0.75A	ATX (note1)	90-260VAC	UL/CSA/TUV
APS-908U	80W	--	6A	3.5A	0.5A	0.5A	--	AT (note1)	85-264VAC	UL/CSA/TUV

Note1: with optional designate cable

Industrial Flex ATX AC Power Supply for 1U Chassis



Model Name	Watt (Typical)	Maximum DC Output Current +3.3V	+5V	+12V	-5V	-12V	+5Vsb	Current Type	AC Voltage Input Range	Certificate
APS-915FXM-ST	150W	10A	15A	0.5A	0.2A	0.5A	1.5A	ATX	90-264VAC	UL/CUL/TUV

All specifications are subject to change without further notice.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000