# Industrial Class Power Supplies

## Industrial Mini-Redundant AC Power Supply



| Model Name | Power (typical) | Maximum DC Output Current | | | | | | AC Voltage Input Range | Certifications |
|---|---|---|---|---|---|---|---|---|---|
| | | +5 V | +3.3 V | +12 V | -12 V | -5 V | +5 Vsb | | |
| APS-946XAR | 460 W | 25 A | 25 A | 30 A | 0.8 A | -- | 2 A | Universal | UL/cUL/TUV/CCC |
| APS-940XAR-EPS12 (for RK-440) | 400 W | 35 A | 25 A | 28 A | 1.2 A | 0.5 A | 2 A | Universal | UL/cUL/TUV/CCC |

- Dimensions: 195 x 150 x 86 (mm)

## Industrial AC Power Supply PS2 Form Factor



| Model Name | Power (typical) | Maximum DC Output Current | | | | | | | AC Voltage Input Range | Certifications |
|---|---|---|---|---|---|---|---|---|---|---|
| | | +5 V | +3.3 V | +12 V1 | +12 V2 | -12 V | -5 V | +5 Vsb | | |
| APS-935XA-EPS12 80 PLUS | 350 W | 20 A | 21 A | 16 A | 16 A | 0.5 A | 0.3 A | 3 A | Universal | UL/cUL/TUV/CCC |
| APS-946XA-EPS12 80 PLUS | 460W | 20 A | 24 A | 16 A | 16 A | 0.5 A | 0.3 A | 3 A | Universal | UL/cUL/TUV/CCC |
| APS-946XA-EPS12 (for RK-440) | 460W | 40 A | 30 A | 32 A | -- | 1 A | 0.8 A | 2 A | Universal | UL/cUL/TUV/CCC |

- Dimensions: Standard PS2 form factor, 140 x 150 x 86 (mm)

## Industrial DC-DC Power Supply PS2 Form Factor



| Model Name | Power (typical) | Maximum DC Output Current | | | | | | DC Voltage Input Range | Certifications |
|---|---|---|---|---|---|---|---|---|---|
| | | +5 V | +3.3 | +12 V | -12 V | -5 V | +5 Vsb | | |
| APS-930/48X | 300 W | 35 A | 30 A | 18 A | 1 A | 0.5 A | 1.5 A | 40 ~ 72 VDC (48 VDC nominal) | UL/cUL/TUV |
| APS-930/24X | 300 W | 30 A | 15 A | 15 A | 2 A | 2 A | 1.2 A | 19 ~ 32 VDC (24 VDC norminal) | UL/CSA/TUV |

- Dimensions: 150 x 140 x 86 (mm)

## Industrial AC Power Supply 1U/2U Form Factor



| Model Name | Power (typical) | Maximum DC Output Current | | | | | | | AC Voltage Input Range | Certifications |
|---|---|---|---|---|---|---|---|---|---|---|
| | | +5 V | +3.3 V | +12 V1 | +12 V2 | -12 V | -5 V | +5 Vsb | | |
| APS-9130XU 80 PLUS | 300 W | 16 A | 14 A | 16 A | 16 A | 0.5 A | 0.3 A | 3 A | Universal | UL/cUL/TUV/CCC |
| APS-9235XU | 350 W | 25 A | 20 A | 28 A | -- | 0.5 A | 0.5 A | 2 A | Universal | UL/cUL/TUV/CCC |

- Dimensions: APS-9130XU: 190 x 100 x 40.5 (mm)
  APS-9235XU: 215 x 100 x 70 (mm)

## Industrial Flex ATX AC Power Supply for Mini-ITX Chassis



| Model Name | Power (typical) | Maximum DC Output Current | | | | | | AC Voltage Input Range | Certifications |
|---|---|---|---|---|---|---|---|---|---|
| | | +5 | +3.3 V | +12 V | -12 V | -5 V | +5 Vsb | | |
| APS-925XU 80 PLUS | 250 W | 14 A | 12 A | 18 A | 0.3 A | -- | 2.5 A | Universal | UL/cUL/TUV/CCC |

- Dimension: 150 x 81.5 x 40.6 (mm)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000