cPCIS-ET2632(R)


3U CompactPCI Subsystem with 8-slot Backplane and 1 + 1 CompactPCI ETT Redundant Power Modules

Features


- 3U CompactPCI® backplane with seven peripheral slots and one system slot
- Temperature, voltage, and fan monitoring LEDs
- Supports current sharing on +5 V, +3.3 V, and +12 V
- 1 + 1 hot swappable 250 W + 250 W CompactPCI® power supplies
- PICMG® 2.11 47-pin power interface
- Hot-swappable cooling fans & filter
- Supports rear I/O backplane with P2 connectors for cPCI 50mm depth RTMs
- cPCI power supply support wide temperature range operation from -20°C to +70°C (-20°C to +50°C at full load with at least 400LFM air flow, power efficiency derating linearly to 50% at +70°C.)

EXTENDED TEMPERATURE





cPCIS-ET2632 Inside Front View



cPCIS-ET2632R Inside Rear View

Ordering Information

Model name	Description
cPCIS-ET2632	3U CPCI Rackmount & Portable sub-system w/ 4U Enclosure Cooling Fans, Alarm, 32-bit 8-slot BP and two ETT 3U PSUs.
cPCIS-ET2632R	3U CPCI Rackmount & Portable sub-system w/ 4U Enclosure Cooling Fans, Alarm, 32-bit 8-slot BP support rear I/O and two ETT 3U PSUs


cPCIS-2633/cPCIS-2833

3U CompactPCI® Subsystem with 13-slot Backplane and 2 + 1 CompactPCI® Redundant Power Modules


Features

- 3U CompactPCI® backplane with 12 peripheral slots and one system slot
- 2 + 1 hot swappable 500 W + 250 W CompactPCI® Power supply (supports three 250 W PSUs)
- Temperature, voltage, and fan monitoring LEDs
- Supports current sharing on +5V, +3.3V, and +12V
- PICMG® 2.11 47-pin power interface
- Hot-swappable cooling fans & filter
- Supports rear I/O backplane with P2 connectors for cPCI 50mm/80mm depth RTMs





cPCIS-2633R/cPCIS-2833R Inside Front View



cPCIS-2633R/cPCIS-2833R Inside Rear View

Ordering Information

Model Name	System	Peripheral	Rear	Alarm Module	PSU QTY	PSU MAX	PICMG®
cPCIS-2633/cPCIS-2833	1	12	1 *system slot only	Yes	3	750 W (2 + 1)	2.0, 2.1, 2.11
cPCIS-2633R/cPCIS-2833R	1	12	13	Yes	3	750 W (2 + 1)	2.0, 2.1, 2.11

Notes: 1. All models above do not include any system or peripheral boards.
2. One cPCI segment, removable PCI to PCI bridge card for bus extension, system slot in the middle.
3. Supports single slot width RTM only in system slot.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

All products and company name listed are trademarks or trade names of their respective companies.
Updated Mar. 10, 2017. ©2017 ADLINK Technology, Inc. All Rights Reserved.
All specifications are subject to change without further notice.