EPS-1132

32-CH Sinking Type Digital Input Module



Specifications

Power Consumption	2.76W
Hot Swap	Yes
Operating Temp.	-20-60 °C
Digital Input /Output Channel	32
Input /Output Type	Sinking
Input Current	IEC-61131-2 Type 1/3
Input Current Limit	2.3mA
Response Time	<1ms
Self-Diagnostic	Power Communication / WDT
Connector Type	Phoenix Contact DFMC

Features

- **32-CH sinking type digital input**
- **Quick removable European type connector**
- **Slave module healthy monitoring**
- **Wide operation temperature range: -20°C - 60°C**
- **Compact size: 100 (L) x 100 (H) mm**
- **IEC-61131 compliant**

Ordering Information

■ **EPS-1132**
32-CH Sinking Type Digital Input Module

EPS-2032

32-CH Sourcing Type Digital Output Module



Specifications

Power Consumption	2.76W
Hot Swap	Yes
Operating Temp.	-20-60 °C
Digital Output Channel	32
Output Type	Sourcing
Output Current (Single Node)	300mA
Output Current (Full node)	1.6A for 8-CH
Response Time	4KHz
Self-Diagnostic	Power / Communication / WDT
Connector Type	Phoenix Contact DFMC

Features

- **32-CH sourcing type digital output**
- **Quick removable European type connector**
- **Slave module healthy monitoring**
- **Wide operation temperature range: -20°C - 60°C**
- **Compact size: 100 (L) x 100 (H) mm**
- **IEC-61131 compliant**

Ordering Information

■ **EPS-2032**
32-CH Sourcing Type Digital Output Module

Updated August 25, 2014. ©2014 ADLINK Technology, Inc. All Rights Reserved. All specifications are subject to change without further notice.