Accessories

LGA775/1156 1U CPU Cooler

- Height: 28 mm
- Fan Speed: 5,500 rpm
- Material: Copper
- Capability: 73W TDP max.
- Backplate included

Ordering Information

- 32-20065-0010: LGA775
- 32-20131-0000: LGA1155/1156



LGA775 3U CPU Cooler

- Height: 62 mm
- Fan Speed: 4,500 rpm
- Material: Aluminum + Copper
- Backplate included

Ordering Information

- 32-20086-0000



Socket-M 1U CPU Cooler

- Height: 22 mm
- Fan Speed: 5,500 rpm
- Material: Copper
- Backplate included

Ordering Information

- 32-20072-0000



LGA1156 2U CPU Cooler

- LGA1155/1156 socket compatible
- Height: 50.2 mm
- Fan Speed: 6100 rpm
- Material: Aluminum + Copper
- Backplate included

Ordering Information

- 32-20113-2000



LGA1156 3U Cooler

- LGA1155/1156 socket compatible
- Height: 65 mm
- Fan Speed: 4,200 rpm
- Material: Aluminum + Copper
- Backplate included

Ordering Information

- 32-20113-0000



HDD Adapter Brackets

Ordering Information

- Two 2.5” HDD in one 3.5” bay: 91-95056-000E
- One 3.5” HDD in one 5.25” bay: 34-30264-1000



Slim DVD Adapter Cable

Ordering Information

- 30-20281-0000



COM Cable

- COM cable with bracket

Ordering Information

- 1 port: 30-25004-0000
- 2 port (2.54mm pitch): 30-25003-0020
- 2 port (2.00mm pitch): 30-25003-1000
- 2 port (for M-302, M-322): 30-25003-4000



USB 2.0 Cable

- 2/4-port USB 2.0 cable with bracket

Ordering Information

- 2-port: 30-25010-1000
- 4-port: 30-25009-2000



2.5” HDD Mobile Rack Kit

- 2x 2.5” HDD in a 3.5” drive bay (tray-less)
- SATA interface
- Black

Ordering Information

- 29-033MA-0000



3.5” HDD Mobile Rack Kit

- 3x 3.5” HDD in two 5.25” drive bay
- SATA interface
- Black

Ordering Information

- 29-033B0-0060



Graphics & Audio Cards

mPCIe-8770

PCIe 2D VGA Display Card

- PCIe VGA Controller XGI™ Volari™ Z11
- PCI Express Spec. compliant
- High Performance 2D Accelerator
- Supports 230 MHz pixel clock
- Supports 4:3 resolution up to 1600x1200, 256/32K/64K/16M colors (70Hz NI)
- Driver support: Windows® 2000, XP, Vista 32/64-bit, 7 32/64-bit; Fedora™ 10, RHEL™ 5



DB-UVGA16

USB Graphics Adapter, internal mount, DB-15 connector


- Mounts in DB9 cutout on chassis or in PCI slot
- Uses internal USB pin header
- Display resolutions up to: 1600 x 1200 (4:3), 1680 x 1050 (16:10)
- Supports multiple display modes: Primary, Extended, Mirror (up to 6 additional monitors)



DB-Audio2

High Definition Audio Daughter Board with Line-in, Line-out and Mic-in

- Realtek ALC262 High Definition Audio codec
- Three jacks: line-in, line-out and mic-in
- 5x2 pin header for cable connection to external audio header on SBC
- 4-pin header interface for CD audio output



LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000