
Peripheral / Communications Cards

PCI-3488/LPCI-3488

High-Performance IEEE488

- *Up to 1.5 MB/s data transfer rate*
- *Supports industrial-standard VISA library*
- *Fully compatible with the IEEE488 standard*
- *Supports a 32-bit 3.3 V or 5 V PCI™ bus*
- *On-board 1 KB FIFO for read/write operations*
- *Provides driver APIs compatible with NI-488.2* driver software*

**NI, LabVIEW, and LabWindows/CVI are trademarks or registered trademarks of National Instruments Corporation or its subsidiaries in the United States and other countries.*



PCI-7841

Dual-port Isolated CAN Interface Card


- *Two independent CAN network operation*
- *Up to 1 Mbps programmable transfer rate*
- *16 MHz CAN controller frequency*
- *2500Vrms isolation protection*
- *Direct memory mapping to the CAN controllers*
- *Powerful master interface for CAN bus protocols*
- *PCI™ bus plug and play*



PCI-8248

Quad Intel® 82546EB Gigabit Ethernet Ports PCI-X™ Card with Bypass Function


- *Quad Gigabit Ethernet Ports*
- *Support PCI-X™ up to 133 MHz*
- *Bypass capability when system power-off or software halt*
- *Software programmable bypass control*
- *Programmable watchdog timer, WDT status read-back*
- *Intel® Boot Agent BIOS*
- *Low-profile bracket is available for OEM programs*



C422/C485

Industrial Intellignt 2/4-Port RS-422/485 Communications Cards

- *PCI™ Rev 2.1 plug and play*
- *Two/four serial communication ports with intelligent buffer*
- *Support isolated RS-422 or RS-485 interface port*
- *Support up to two cards per system*
- *Suitable for modems, data display, data collection, telecommunication and industry control*
- *Support Windows® NT/95/98/2000/XP and Linux® operating systems*



C422

C485

PCI-8246

Dual Intel® 82546EB Gigabit Ethernet Ports PCI-X™ Card with Bypass Function


- *Dual Gigabit Ethernet Ports*
- *Support PCI-X™ up to 133 MHz*
- *Bypass capability when system power-off or software halt*
- *Software programmable bypass control*
- *Programmable watchdog timer, WDT status read-back*
- *Intel® Boot Agent BIOS*
- *Low-profile bracket is available for OEM programs*



C518/C514

Industrial 8/4-Port Serial Communications Cards

- *PCI™ Rev 2.1 plug and play*
- *Four/eight serial communication ports*
- *Suitable for modems, data display, data collection, telecommunication and industry control*
- *Support one isolated RS-422 or RS-485 interface port*
- *Support up to 8 cards per system*
- *Support Windows® 95/98/NT/2000/XP and Linux® operating systems*



C518

C514

PCI-8213/8214

Quad/Dual Intel® 82559 10/100 Mbps Ethernet 64-bit/66 MHzPCI Cards

- *32/64-bits, 33/66 MHz PCI bus*
- *Four/Two Intel 82559 high performance 10/100-BaseTX Ethernet controllers*
- *Built-in watch-dog timer for bypass feature, which can bypass the Ethernet ports while no-power or system fault automatically (PCI-8214)*
- *Supports IEEE 802.3u auto-negotiation for 10Base-T /100Base-TX*
- *Supports IEEE 802.3x 100Base-TX flow control*
- *Reserved extra pin-header for LAN status LED for panel-free design*
- *Driver supporting Windows® 95/98/NT/2000/XP, Linux®*




PCI-8213

C588/C584

Industrial Intelligent 8/4-Port Serial Communications Cards

- *PCI™ Rev 2.1 plug and play*
- *Four/eight serial communication ports*
- *Suitable for modems, data display, data collection, telecommunication and industry control*
- *Support up to two cards per system and Jumper-less, easy to configure*
- *Optional isolated RS-422/485 interface box for each port independently*
- *Support Windows® NT/95/98/2000/XP and Linux® operating systems*



C588

C584

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000