ADLINK
LEADING EDGE COMPUTING

3U CompactPCI Serial 2-Port serial Card

cPCI-A3COM

Datasheet



cPCI-A3COM

Features

- Follow PICMG® CompactPCI® Serial design guide
- CompactPCI® Serial, 3U 4HP
- 2x DB9 COM ports in front panel
- Operating temperature: -40°C to +85°C
- Designed to meet EN50155 standards

Specifications

Interface	Serial port	2x DB9 ports, support RS232/422/485
	Form Factor	3U 4HP CPCI-S.0 standard, with P1, P3 & P4 to rear.
Power	Power Input	12V +/- 10% Max
	Power Consumption	TBC Watt
Mechanical	Dimensions	3U 1-slot 4HP 100 x 160 x 20.32 mm (L x W x H)
	Net Weight	0.26kg
Environment & Certification	Operating Temperature	-40°C ~ 85° when provided with airflow
	Humidity operating	5% to 95% relative humidity (non-condensing)
	EMC	EN55032 Class A / EN55035 IEC61000-6-2/3/4/5/6/8 FCC Part 15B CLASS A
	Environmental	RoHS 2.0 & REACH

Ordering Information

cPCI-A3COM	3U CompactPCI Serial COM port card, two COM ports support RS232/422/485
Recommended CPU Board	
cPCI-A3525	3U CompactPCI Serial 9th Gen Intel Xeon®/Core™ i7 Processor Blade
cPCI-A3535	3U CompactPCI Serial Intel® Xeon® W Processor Blade

www.adlinktech.com

intel partner Titanium IoT Solutions

All products and company names listed are trademarks or trade names of their respective companies. ©2024 ADLINK Technology, Inc. All Rights Reserved. All pricing and specifications are subject to change without further notice.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000