ADLINK
LEADING EDGE COMPUTING

3U CompactPCI® Serial XMC module Carrier Blade

cPCI-A3XMC

Datasheet



Features

- 3U 4HP CPCI-S.0 peripheral
- One XMC slot
- Operating temperature: -40°C to 85°C with qualified components

Specifications

General	XMC	1x XMC connector via PCIe x4
	PICMG Standards	CompactPCI® Serial Rev 2.0
Backplane Interfaces	PCI Express	1x PCIe x4 Gen3 on P1
Electrical Specifications	Power Input	+12V
Mechanical & Environmental	Form Factor	3U 4HP 1-slot CompactPCI Serial blade 160mm x 100mm (LxW) Equipped with P1
	Weight	0.2g (without XMC)
	Operating Temp.	-40°C to +70°C with air cool (selected extend temperature XMC module)
	Storage Temp.	-40°C to +85°C

Ordering Information

cPCI-A3XMC	3U CompactPCI Serial XMC module carrier

www.adlinktech.com

intel partner Titanium IoT Solutions

All products and company names listed are trademarks or trade names of their respective companies. ©2022 ADLINK Technology, Inc.
All Rights Reserved. All pricing and specifications are subject to change without further notice.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000