HSL-AO4-U

4-CH Analog Output Module



Features

- **4-CH analog output**
- **Output voltage range selection ±12 V**
- **16-bit resolution**
- **Isolation voltage: 2500 VRMS**
- **Easy programming by software**
- **Easy installation and wiring**

Software Support

- **Windows® Platform**

  Windows® 7/Vista (32-bit)/XP/2000 libraries

- **HSL LinkMaster Utility**

  The HSL LinkMaster utility is used to scan and test slave devices.

Specifications

Slave ID Consumption	2
Transmission Mode	Full/Half duplex
Transmission Speed	3/6/12 Mbps selectable, 6 Mbps is default setting
Analog Output Channel	4
Circuit Type	Single-ended
D/A Resolution	16-bit
Output Range	± 12 V
D/A Settling Time	10 μs (max.)
D/A Offset Error	0.5 mV (max.)
LED Indicator	Power and Link
Power Requirement	+24 VDC (±10%)

Ordering Information

- **HSL-AO4-U**

  4-CH analog output module

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Updated 03-28, 2012. ©2012 ADLINK Technology, Inc. All Rights Reserved. All specifications are subject to change without further notice.