LEC-Starterkit R2



Features

- SMARC compliant LEC-BASE R1 carrier board
- SD card and USB stick
- Interface cables (one way open) for camera, GPIO, power management, SPI, I²C and LVDS
- AC/DC adapter, power cord and universal socket

SMARC *LEC = Low Energy Computer-on-Module

Contents

Standard Items

- SMARC compliant LEC-BASE R1 carrier board (see extra data sheet for features)
- SD card, 4GB SDHC Card (Class 10)
- USB stick (8GB USB2.0 flash drive)
- Interface cables for camera, GPIO, power management, SPI, I²C and LVDS
- AC/DC adapter, 19V, 4.7A
- Power cord, 7A at 125V (USA)
- Universal socket to EU plug, 10-16A, 250V (female)
- Universal power socket (male): EU plug

Extra Mandatory Order

Modules

LEC-BW, LEC-BT or LEC-BTS

Heatspreader

Heatspreader for LEC-BW, LEC-BT or LEC-BTS

Software

BSP depending on operating system

Ordering Information

Model Number	Description/Configuration
LEC-Starterkit R2	LEC-Starterkit with LEC-BASE R1 carrier board, including SD card and power supply (without LEC module and cooling solution)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000