ADLINK
LEADING EDGE AI COMPUTING

COM-HPC Mini Dev Kit
Intel® Panther Lake

COM-HPC Mini Dev Kit with Intel® Core™ Ultra X7/7 358H/356H Processors



Features

- Powered by Intel® Core™ Ultra X7/7 processors with advanced AI acceleration
- Features COM-HPC-mMTL for compact and high-performance applications
- Bundled with COM-HPC R1.2 Type Mini carrier board in standard ATX form factor
- Support industrial-grade design with 10-year longevity
- Compatible with Windows® 11 and Ubuntu for embedded solutions

Specifications

Core System	SoC	Processor	Cores/Threads	Cache	TDP
		Intel® Core™ Ultra X7 358H	4P+8E+4LPE/16T	18MB	25W
		Intel® Core™ Ultra 7 356H	4P+8E+4LPE/16T	18MB	25W
	Architecture	X86			
	Memory	64GB LPDDR5x, dual-channel memory, up to 9600 MT/s (onboard memory)			
	Embedded BIOS	AMI UEFI with CMOS backup in 32MB SPI BIOS			
	IoT Security	TPM 2.0, Intel® AES-NI, Secure Key, Execute Disable Bit, OS Guard, and Boot Guard			
Graphics	GPU Core	Intel® Xe Low Power Graphics			
	Video Decoding	AV1, HEVC (8/10-bit), H.264, VP9, VP8, MPEG-2, VC-1, MJPEG			
	Video Encoding	AV1, HEVC (8/10-bit), H.264, VP9, VP8, MJPEG			
	Multi-Display	Quad Independent Display			
Audio	Chipset	Integrated on SoC			
	Codec	Realtek ALC888S			

Note: “Build option” indicates an alternative BOM configuration to support additional or alternative functions that are not available on the standard product. Be aware that these “build option” part numbers will need to be newly created and this will result in production lead times.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Specifications

Ethernet	LAN	Intel i226 controller with 10/100/1000/2500M speed
Connectors /Headers	Display	1x eDP port (internal) 1x DP port (rear)
	USB	2x USB4 Type C (rear) 2x USB3.2 gen2 Type A (rear) 2x USB2.0 Type A (rear) 2x USB 2.0 w/ 1 pin header (internal)
	Network	2x RJ45 Note: NBASE-T_1 is muxed with PCIe lane7/SATA port 0; the default is NBASE-T_1.
	Audio	3x jacks (Mic-in/Line-in/Line-out)
	Buttons	1x power button 1x reset button 1x sleep button
	Expansion Slots	1x PCIex8 slot Note: An add-on card is required for 2 PCIe x4 signals 1x PCIex4 slot 1x M.2 M-key connector (PCIe lane 4-7)
	FAN	1x CPU fan header (4-pin, from module) 2x system FAN headers (4-pin, from SIO)
	GPIO	1x 12-bit GPIO connector
	Serial	2x COM port box headers (10-pin, from module) 2x COM port box headers (10-pin, from SIO)
	Management Buses	1x SMBus header 2x I²C headers 1x eSPI header
	Secondary BIOS	1x secondary SPI flash socket (optional)
LEDs	POST LED	Onboard I/O expander for BIOS POST code via I²C bus
Power	Standard Input	AT mode 12V±5%; Vin 8-20V (single power rail)
	Connector	ATX 24+4pin
Operating Systems	Windows	Windows 11 IoT Enterprise LTSC
	Linux	Ubuntu 26.04 LTS

Note: “Build option” indicates an alternative BOM configuration to support additional or alternative functions that are not available on the standard product. Be aware that these “build option” part numbers will need to be newly created and this will result in production lead times.


Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Ordering Information

Module	
COM-HPC-mPTL-358H-16G-Kit	COM-HPC Mini Dev Kit with COM-HPC-mPTL-358H-16G, with carrier, THSF, and accessories
COM-HPC-mPTL-356H-16G-Kit	COM-HPC Mini Dev Kit with COM-HPC-mPTL-358H-16G, with carrier, THSF, and accessories

Note: For certain processor or memory capacity SKUs not listed, please contact our ADLINK representative.

Mechanical Layout



All products and company names listed are trademarks or trade names of their respective companies. Updated October 12, 2026. ©2026 ADLINK Technology, Inc. All Rights Reserved. All pricing and specifications are subject to change without further notice.