MXC-6600 Series

High Performance
9th Generation Intel® Xeon®/Core™ i7/i3 &
8th Gen Intel® Core™ i5 Processor-Based
Fanless Expandable Computer

MXC-6620/MXC-6640

User's Manual



Manual Rev.: 1.0

Revision Date: Sept. 14, 2020

Part No: 50-1Z330-1000

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Leading **EDGE COMPUTING**

Revision History

Revision	Release Date	Description of Change(s)
1.0	2020-09-14	Initial release

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Preface

Copyright © 2020 ADLINK Technology Inc.


This document contains proprietary information protected by copyright. All rights are reserved. No part of this manual may be reproduced by any mechanical, electronic, or other means in any form without prior written permission of the manufacturer.

Disclaimer

The information in this document is subject to change without prior notice in order to improve reliability, design, and function and does not represent a commitment on the part of the manufacturer.

In no event will the manufacturer be liable for direct, indirect, special, incidental, or consequential damages arising out of the use or inability to use the product or documentation, even if advised of the possibility of such damages.

Environmental Responsibility



ADLINK is committed to fulfill its social responsibility to global environmental preservation through compliance with the European Union's Restriction of Hazardous Substances (RoHS) directive and Waste Electrical and Electronic Equipment (WEEE) directive. Environmental protection is a top priority for ADLINK. We have enforced measures to ensure that our products, manufacturing processes, components, and raw materials have as little impact on the environment as possible. When products are at their end of life, our customers are encouraged to dispose of them in accordance with the product disposal and/or recovery programs prescribed by their nation or company.

Battery Labels (for products with battery)



LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

California Proposition 65 Warning

WARNING: This product can expose you to chemicals including acrylamide, arsenic, benzene, cadmium, Tris(1,3-dichloro-2-propyl) phosphate (TDCPP), 1,4-Dioxane, formaldehyde, lead, DEHP, styrene, DINP, BBP, PVC, and vinyl materials, which are known to the State of California to cause cancer, and acrylamide, benzene, cadmium, lead, mercury, phthalates, toluene, DEHP, DIDP, DnHP, DBP, BBP, PVC, and vinyl materials, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Trademarks

Product names mentioned herein are used for identification purposes only and may be trademarks and/or registered trademarks of their respective companies.

Conventions

Take note of the following conventions used throughout this manual to make sure that users perform certain tasks and instructions properly.

NOTE: Additional information, aids, and tips that help users perform tasks.

CAUTION: Information to prevent ***minor*** physical injury, component damage, data loss, and/or program corruption when trying to complete a task.
ATTENTION: Informations destinées à prévenir les blessures corporelles mineures, les dommages aux composants, la perte de données et/ou la corruption de programme lors de l'exécution d'une tâche.

WARNING: Information to prevent ***serious*** physical injury, component damage, data loss, and/or program corruption when trying to complete a specific task.
AVERTISSEMENT: Informations destinées à prévenir les blessures corporelles graves, les dommages aux composants, la perte de données et/ou la corruption de programme lors de l'exécution d'une tâche spécifique.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Table of Contents

Preface iii

List of Tables vii

List of Figures ix

1 Introduction 1
- 1.1 Overview 1
- 1.2 Features 1
- 1.3 Packing List 2
- 1.4 Optional Accessories 2

2 Specifications 3
- 2.1 MXC-662X/MXC-664X/MXC-6621/MXC-6641 3
- 2.2 MXC-6622/MXC-6642/MXC-6623/MXC-6643 5
- 2.3 MXC-6600 Series Functional Block Diagram 7
- 2.4 Display Options 8
- 2.5 Mechanical Dimensions 9

3 System Layout 15
- 3.1 Front Panel 15
- 3.2 Internal I/O Connectors 26

4 Getting Started 33
- 4.1 Attach DC Power Connector 33
- 4.2 Mounting the MXC-6600 Series 34
- 4.3 Driver Installation 36

A Appendix: Power Consumption 37
- A.1 Power Consumption Reference 37

B Appendix: BIOS Setup 39

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.1 Main 40
B.2 Advanced 41
B.3 Chipset 56
B.4 Security 67
B.5 Boot 69
B.6 Save & Exit 71

C Appendix: Watchdog Timer (WDT) Function Library 73
C.1 WDT with API/Windows 73
C.2 WDT with DOS/Linux 76

D Appendix: Digital Input/Output Function Library 79

Important Safety Instructions..... 87

Consignes de Sécurité Importante 89

Getting Service 93

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

List of Tables

Table 2-1: Maximum Display Resolution Configurations 8
Table 3-1: Front Panel I/O Legend 15
Table 3-2: LED Indicators 16
Table 3-3: DisplayPort Pin Definition 17
Table 3-4: Applicable Cable Types 18
Table 3-5: Digital Input/Output Connector Pin Definition 19
Table 3-6: HDMI Connector Pin Definition 20
Table 3-7: Ethernet Port Pin Definition 22
Table 3-8: Active/Link LED Indicators 22
Table 3-9: Speed LED Indicators 22
Table 3-10: DC Power Input Pin Definition 23
Table 3-11: D-Sub 9-pin Signal Function of COM Ports 24
Table 3-12: Mainboard Connector Legend 27
Table 3-13: 2-slot Backplane Board Connector Legend 28
Table 3-14: 4-slot Backplane Board Connector Legend 29
Table 3-15: GPS Module Power Header Pin Definition 30
Table 3-16: 12V Fan Connector Pin Definition 31
Table 3-17: PWR/RESET Header Pin Definition 32
Table 3-18: 12V Power Pin Definition 32
Table A-1: Power Consumption 37

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

This page intentionally left blank.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

List of Figures

Figure 2-1: MXC-6600 Series Functional Block Diagram 7
Figure 2-2: MXC-6620 Front View 9
Figure 2-3: MXC-6640 Front View 10
Figure 2-4: MXC-6620/6640 Left Side View..... 11
Figure 2-5: MXC-6620/6640 Right Side View 12
Figure 2-6: MXC-6620/6640 Top View (with wall-mount brackets).. 13
Figure 3-1: Front Panel I/O 15
Figure 3-2: DisplayPort Connector Pin Definition..... 17
Figure 3-3: Digital I/O Connector Pin Definition 18
Figure 3-4: Digital Input Circuit..... 19
Figure 3-5: Digital Output Circuit..... 20
Figure 3-6: Ethernet Port and LEDs..... 22
Figure 3-7: DC Power Input 23
Figure 3-8: COM Port Pin Definition..... 24
Figure 3-9: CFast Host Slot..... 25
Figure 3-10: Mainboard Connectors 26
Figure 3-11: 2-slot Backplane Board Connectors 28
Figure 3-12: 4-slot Backplane Board Connectors 29
Figure 3-13: GPS Module Power Header Pin Definition 30
Figure 3-14: 12V Fan Connector Pin Definition 31
Figure 3-15: Clear CMOS Jumper Setting 31
Figure 3-16: PWR/RESET Header Pin Definition 32
Figure 3-17: 12V Power Pin Definition..... 32

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

This page intentionally left blank.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

1 Introduction

1.1 Overview

The MXC-6600 Series provides powerful, fanless, expandable embedded computing using the new 9th Gen Intel® Xeon®, Core™ i7/i3 and 8th Gen Intel® Core™ i5 processors with improved computing performance. The MXC-6600 continues the exceptional fanless design from the existing Matrix C series and offers a rich I/O experience with dual DisplayPorts, and an HDMI port supporting three independent displays, two USB3.1 Gen2 ports, two USB 3.1 Gen1, six USB 2.0 and two GbE LAN ports with adapter teaming support. The built-in 16-channel DI/O enables general industrial control, while PCI & PCI express (Gen3) expansion slots accept a variety of PCI, PCIe x8, and PCIe x16 add-on cards for platform development operations. Compared to other industrial PCs, the MXC-6600 Series is more compact and reliable with superior dependability in harsh environments where severe temperature variation and vibration may occur. The MXC-6600 Series provides an optional hot-pluggable fan module to dissipate heat from the system when high power consumption PCI/PCIe cards are installed. Additional function boards can be customized according to customer I/O needs. The Matrix MXC-6600 Series provides a more robust mechanical design, easy installation, and supports a greater variety of I/O options.

1.2 Features

- 9th Gen Intel® Xeon®, Core™ i7/i3 and 8th Gen Intel® Core™ i5 Processor-Based Embedded Fanless Computer
- Dual DDR4 SODIMMs up to 32GB
- Rich I/O: 2x DP++, 1x HDMI, 2x GbE, 6x COM, 8-ch DI, 8-ch DO, TPM 2.0
- 2x USB 3.1 Gen 2, 2x USB 3.1 Gen1 , 4x USB 2.0
- Rich storage: up to 4 internal 2.5" SATA 6 Gb/s ports with RAID 0/1/5/10 support, CFast, M.2 2280
- Embedded expansion: 1x Mini PCIe, 1x M.2 3042, 2x USIM

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

- Front accessible I/O and adaptive function module v.2 (optional)
- 5x user-defined LEDs
- Flexible modular expansion with 2 or 4 slots

1.3 Packing List

Before unpacking, check the shipping carton for any damage. If the shipping carton and/or contents are damaged, inform your dealer immediately. Retain the shipping carton and packing materials for inspection. Obtain authorization from your dealer before returning any product to ADLINK. Ensure that the following items are included in the package.

- MXC-6600 Series Fanless Embedded Computer
- Accessory Box
  - DC power jack
  - Wall-mount brackets
  - Screw pack

1.4 Optional Accessories

- AC/DC Adapter
  - 220W (P/N: 31-62149-0000)
  - 280W (P/N: 91-95263-0010)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

2 Specifications

2.1 MXC-662X/MXC-664X/MXC-6621/MXC-6641

	MXC-662X	MXC-664X	MXC-6621	MXC-6641
System Core				
Processor	Intel® Xeon® E-2276ME 45W		Intel® Core™ i7-9850HE 45W	
Chipset	Mobile Intel® CM246			
Memory	4GB DDR4 2400MHz, dual SODIMMs, up to 32GB			
I/O Interface				
Display	2x DP++, 1x HDMI			
Expansion Slots	PCIe x16 + PCIe x4	PCIe x16 + 2 PCIe x4 + PCI	PCIe x16 + PCIe x4	PCIe x16 + 2 PCIe x4 + PCI
Ethernet	2x Intel GbE: 1x i211AT + 1x i219 iAMT support			
Serial Ports	COM1/2: RS-232/422/485 COM3/4/5/6: RS-232			
USB	2x USB 3.1 Gen 2, 2x USB 3.1 Gen 1, 4x USB 2.0, 1x internal USB 2.0 dongle			
Audio	Line-out, Mic-in (optional: speaker-out)			
Mini PCIe	1x Full size (USB 2.0 + PCIe)			
M.2	1x socket 2, key B+M or B, 2280/3042: USB 3.1 Gen 1, SATA 6 Gb/s and PCIe x2 supporting NVMe			
USIM	2x (1x for Mini PCIe and 1x for M.2)			
DI/O	8-ch DI and 8-ch DO			
I^2C	2x (3.3V/5V)			
TPM 2.0	Supported			
Storage				
2.5" SATA	2x internal (extra 2 w/ optional kit, supports RAID 0/1/5/10)			
CFast	1x Type II			
Physical				
Dimensions	165 (W) x 240 (D) x 210 (H) mm (6.5" x 9.45" x 8.27")	206 (W) x 240 (D) x 210 (H) mm (8.11" x 9.45" x 8.27")	165 (W) x 240 (D) x 210 (H) mm (6.5" x 9.45" x 8.27")	206 (W) x 240 (D) x 210 (H) mm (8.11" x 9.45" x 8.27")
Weight	4.6 kg (10.2 lb.)	4.9 kg (10.8 lb.)	4.6 kg (10.2 lb.)	4.9 kg (10.8 lb.)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

	MXC-662X	MXC-664X	MXC-6621	MXC-6641
Mounting	Wall mount			
Power Supply				
DC Input	9-32V DC (± 10% tolerance)			
AC Input	Optional: 220W/280W AC/DC adapter			
Environmental				
Operating Temperature	Standard: 0°C to 50°C (32°F to 122°F) w/ airflow			
	Extended: (w/ ind. storage, airflow) -20°C to 70°C (-4°F to 158°F) (w/ single SODIMM) -20°C to 60°C (-4°F to 140°F) (w/ dual SODIMMs)			
Storage Temperature	-40°C to 85°C (-40°F to 185°F) excluding storage			
Humidity	approx. 95% @ 40°C (104°F) non-condensing			
Vibration	Operating: 5 Grms, 5-500 Hz, 3 axes (w/ SSD/CFast) Operating: 0.5 Grms, 5-500 Hz, 3 axes (w/ HDD)			
Shock	Operating: 100 G, half sine 11ms duration (w/ SSD/CFast)			
ESD	Contact +/-8kV, Air +/-15kV			
EMC	EN61000-6-4/-2, CE & FCC Class B with validated AC/DC adapter			
Safety	UL/cUL, CB			

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

2.2 MXC-6622/MXC-6642/MXC-6623/MXC-6643

	MXC-6622	MXC-6642	MXC-6623	MXC-6643
System Core				
Processor	Intel® Core™ i5-8400H 45W		Intel® Core™ i3-9100HL 25W	
Chipset	Mobile Intel® CM246			
Memory	4GB DDR4 2400MHz, dual SODIMMs, up to 32GB			
I/O Interface				
Display	2x DP++, 1x HDMI			
Expansion Slots	PCIe x16 + PCIe x4	PCIe x16 + 2 PCIe x4 + PCI	PCIe x16 + PCIe x4	PCIe x16 + 2 PCIe x4 + PCI
Ethernet	2x Intel GbE: 1x i211AT + 1x i219 iAMT support			
Serial Ports	COM1/2: RS-232/422/485 COM3/4/5/6: RS-232			
USB	2x USB 3.1 Gen 2, 2x USB 3.1 Gen 1, 4x USB 2.0, 1x internal USB 2.0 dongle			
Audio	Line-out, Mic-in (optional: speaker-out)			
Mini PCIe	1x Full size (USB 2.0 + PCIe)			
M.2	1x socket 2, key B+M or B, 2280/3042: USB 3.1 Gen 1, SATA 6 Gb/s, and PCIe x2 supporting NVMe			
USIM	2x (1x for Mini PCIe and 1x for M.2)			
DI/O	8-ch DI and 8-ch DO			
I^2C	2x (3.3V/5V)			
TPM 2.0	Supported			
Storage				
2.5" SATA	2x internal (extra 2 w/ optional kit, supports RAID 0/1/5/10)			
CFast	1x Type II			
Physical				
Dimensions	165 (W) x 240 (D) x 210 (H) mm (6.5" x 9.45" x 8.27")	206 (W) x 240 (D) x 210 (H) mm (8.11" x 9.45" x 8.27")	165 (W) x 240 (D) x 210 (H) mm (6.5" x 9.45" x 8.27")	206 (W) x 240 (D) x 210 (H) mm (8.11" x 9.45" x 8.27")
Weight	4.6 kg (10.2 lb.)	4.9 kg (10.8 lb.)	4.6 kg (10.2 lb.)	4.9 kg (10.8 lb.)
Mounting	Wall mount			
Power Supply				
DC Input	9-32V DC (± 10% tolerance)			

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

	MXC-6622	MXC-6642	MXC-6623	MXC-6643
AC Input	Optional: 220W/280W AC/DC adapter			
Environmental				
Operating Temperature	Standard: 0°C to 50°C (32°F to 122°F) w/ airflow			
	Extended: (w/ ind. storage, airflow) -20°C to 70°C (-4°F to 158°F) (w/ single SODIMM) -20°C to 60°C (-4°F to 140°F) (w/ dual SODIMMs)			
Storage Temperature	-40°C to 85°C (-40°F to 185°F) excluding storage			
Humidity	approx. 95% @ 40°C (104°F) non-condensing			
Vibration	Operating: 5 Grms, 5-500 Hz, 3 axes (w/ SSD/CFast) Operating: 0.5 Grms, 5-500 Hz, 3 axes (w/ HDD)			
Shock	Operating: 100 G, half sine 11ms duration (w/ SSD/CFast)			
ESD	Contact +/-8kV, Air +/-15kV			
EMC	EN61000-6-4/-2, CE & FCC Class B with validated AC/DC adapter			
Safety	UL/cUL, CB			

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

2.3 MXC-6600 Series Functional Block Diagram




Figure 2-1: MXC-6600 Series Functional Block Diagram

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

2.4 Display Options


With computing and graphic performance enhancement from its 8th & 9th Generation Intel processors, the MXC-6600 Series controller can support three independent displays, with configurations as follows.

Display Option 1	DisplayPort1 4096x2304@60Hz
Display Option 2	DisplayPort2 4096x2304@60Hz
Display Option 3	HDMI 1.4 (Native) 4096x2160@30Hz

Table 2-1: Maximum Display Resolution Configurations

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


2.5 Mechanical Dimensions



(units: mm)

Figure 2-2: MXC-6620 Front View


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



(units: mm)

Figure 2-3: MXC-6640 Front View


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



(units: mm)

Figure 2-4: MXC-6620/6640 Left Side View


Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



(units: mm)

Figure 2-5: MXC-6620/6640 Right Side View

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



(units: mm)

Figure 2-6: MXC-6620/6640 Top View (with wall-mount brackets)

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

This page intentionally left blank.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3 System Layout

3.1 Front Panel

The MXC-6600 Series provides the following front panel access features.




Figure 3-1: Front Panel I/O

A	DC Power Input	**I**	Extend Power Button
B	DisplayPort x2	**J**	Power
C	HDMI	**K**	Reset
D	USB 3.1 Gen 2 (Type-A) x2	**L**	Audio (Mic, Phones/Speaker)
E	Gigabit Ethernet x2	**M**	Digital Input/Output
F	USB 3.1 Gen 1 (Type-A) x2	**N**	CFast
G	USB 2.0 (Type-A) x4	**O**	COM Port x6
H	LED Indicators		

Table 3-1: Front Panel I/O Legend

3.1.1 Power Button

The power button is a non-latched push button with a blue LED indicator. System is turned on when the button is depressed, and the power LED lights. If the system hangs, depress the button for 5 seconds to turn off the system completely.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.1.2 LED Indicators

In addition to the LED of the power button, three LEDs on the front panel indicate the following.

LED Indicator	Color	Description
Watchdog (WD)	Yellow	Indicates watchdog timer status. When watchdog timer starts, the LED flashes. When the timer is expired, the system will auto reboot.
Hard disk drive (HD)	Orange	Indicates the HDD operating state. When the SATA hard drive or CFast card is active, the LED indicator flashes.
Diagnostic (DG)	Green	When lit continuously, indicates no physical storage is connected, and if blinking, indicates no memory is installed on either SODIMM socket.
User defined (U1)	Red	User defined LED
User defined (U2)	Green	User defined LED
User defined (U3)	Green	User defined LED
User defined (U4)	Green	User defined LED
User defined (U5)	Green	User defined LED

Table 3-2: LED Indicators

3.1.3 PCI Slot

The MXC-6640 provides one PCI slot for expansion on the back-plane board. Based on the ITE IT8892E PCIe to PCI bridge, connection to the host system is achieved through a PCIe x1 Gen3 interface, supporting universal or 5V PCI 32-bit cards operating at 33MHz clocks.

3.1.4 PCI Express x16 Slot

One PCI Express x16 slot supports expansion with standard PCIe Gen3 cards and full PCI express x16 signals.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.1.5 PCI Express x4 Slot

Two PCI Express x4 slots support expansion with standard PCIe Gen3 cards and full PCI express x4 signals.

3.1.6 Reset Button

The reset button executes a hard reset for the MXC-6600 Series.

3.1.7 DisplayPort Connectors

Two DisplayPort connectors on the front panel can connect to VGA, DVI, HDMI and DisplayPort monitors via DisplayPort to VGA adapter cable, DisplayPort to DVI adapter cable, or DisplayPort to HDMI adapter cable and DisplayPort cable.




Figure 3-2: DisplayPort Connector Pin Definition

Pin	Signal	Pin	Signal
1	CN_DDPx0+	11	GND
2	GND	12	CN_DDPx3-
3	CN_DDPx0-	13	CN_DDPx_AUX_SEL
4	CN_DDPx1+	14	CN_DDPx_CONFIG2
5	GND	15	CN_DDPx_AUX+
6	CN_DDPx1-	16	GND
7	CN_DDPx2+	17	CN_DDPx_AUX-
8	GND	18	CN_DDPx_HPD
9	CN_DDPx2-	19	GND
10	CN_DDPx3+	20	+V3.3_DDPx_PWR_CN

Table 3-3: DisplayPort Pin Definition

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

P/N	Description
30-01119-0020	Passive DisplayPort to HDMI adapter cable
30-01120-0020	Passive DisplayPort to DVI adapter cable
30-01121-0020	Passive DisplayPort to VGA adapter cable
30-01157-0020	Active DisplayPort to DVI adapter cable

Table 3-4: Applicable Cable Types

3.1.8 Digital I/O Connector

The MXC-6600 Series provides 8 channels of non-isolation digital input and 8 channels of non-isolation digital output circuits, with the following specifications.

8-channel Digital Input

- VIH: 2 to 5.25V
- VIL: 0 to 0.8V

8-channel Digital Output

- Output type: Open drain N-channel
- MOSFET driver with internal pull high of 200Ω resistance
- Source/Sink current for all channels: 24mA
- VOH: 2.4 to 5V
- VOL: 0 to 0.5V




Figure 3-3: Digital I/O Connector Pin Definition

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Pin	Signal	Pin	Signal	Pin	Signal	Pin	Signal
1	DI0	8	DI7	15	N/C	22	DO3
2	DI1	9	GND	16	N/C	23	DO4
3	DI2	10	N/C	17	N/C	24	DO5
4	DI3	11	N/C	18	GND	25	DO6
5	DI4	12	N/C	19	DO0	26	DO7
6	DI5	13	N/C	20	DO1		
7	DI6	14	N/C	21	DO2		

Table 3-5: Digital Input/Output Connector Pin Definition




Figure 3-4: Digital Input Circuit

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000





Figure 3-5: Digital Output Circuit

3.1.9 HDMI Connector

The MXC-6600 Series provides one HDMI connector for connection to an external monitor.



Pin #	Signal	Pin #	Signal
1	CON_HDMI_TX2_P	2	GND
3	CON_HDMI_TX2_N	4	CON_HDMI_TX1_P
5	GND	6	CON_HDMI_TX1_N
7	CON_HDMI_TX0_P	8	GND
9	CON_HDMI_TX0_N	10	CON_HDMI_CLK_P
11	GND	12	CON_HDMI_CLK_N
13	N/C	14	N/C
15	DVI_SCL_SINK	16	DVI_SDA_SINK
17	GND	18	P_+5V0_HDMI_CN
19	CON_HDMI_HPD_5V0		

Table 3-6: HDMI Connector Pin Definition

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.1.10 USB 2.0 Ports

The MXC-6600 Series provides four front panel USB 2.0 Type-A ports. All USB ports are compatible with high-speed, full-speed and low-speed USB devices. The MXC-6600 Series supports multiple boot devices, including USB flash drive, USB external hard drive, USB floppy, USB CD-ROM and others. The boot priority and boot device can be configured in the BIOS.

3.1.11 USB 3.1 Ports

The MXC-6600 Series provides two USB 3.1 Gen 2 and two USB 3.1 Gen 1 ports supporting Type-A USB 3.1 connection on the front panel. All USB 3.1 ports are compatible with super-speed Gen 1, high-speed, full-speed and low-speed USB devices, except USB 3.1 port #1 & #2, which support only USB 3.1 Gen 2 devices.

3.1.12 Gigabit Ethernet Ports

Two Gigabit Ethernet ports on the front panel support Intel WGI211AT and WGI219LM Gigabit Ethernet PHY controller and connection, providing

- IEEE 802.3az Energy Efficient Ethernet
- IEEE 1588/802.1AS precision time synchronization
- IEEE 802.3Qav traffic shaper
- Interrupt moderation, VLAN support, IP checksum offload
- RSS and MSI-X to lower CPU utilization in multi-core systems
- ECC - error correcting memory in packet buffers
- Wake-On-LAN
- Preboot eXecution Environment (PXE) flash interface
- Jumbo frame support

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Speed LED Green/Orange	Active/Link Yellow




Figure 3-6: Ethernet Port and LEDs

Pin #	10BASE-T/ 100BASE-TX	1000BASE-T
1	TX+	LAN_TX0+
2	TX-	LAN_TX0-
3	RX+	LAN_TX1+
4	—	LAN_TX2+
5	—	LAN_TX2-
6	RX-	LAN_TX1-
7	—	LAN_TX3+
8	—	LAN_TX3-

Table 3-7: Ethernet Port Pin Definition

LED Color	Status	Description
Yellow	OFF	Ethernet port is disconnected.
	ON	Ethernet port is connected with no activity.
	Flashing	Ethernet port is connected and active.

Table 3-8: Active/Link LED Indicators

LED Color	Status	Description
Green/Orange	OFF	10 Mbps
	Green	100 Mbps
	Orange	1000 Mbps

Table 3-9: Speed LED Indicators

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.1.13 DC Power Input




Figure 3-7: DC Power Input

Pin	Signal
1	V+ (DC_IN)
2	V- (DGND)

Table 3-10: DC Power Input Pin Definition

Refer to Section 4.1: Attach DC Power Connector on page 33 to install the DC Power Connector to the DC Power Input.

Please use an approved power source as certified by IEC or UL. The maximum ambient operating temperature (Tma) is described in “Important Safety Instructions”. Altitude during operation is up to 2000 m where output meets LPS and SELV circuit requirements.

Power Source Rating

	Voltage	Current
DC Power Source	9 to 32V DC	29A to 8.75A min.
AC-to-DC Adapter	24VDC	11.6A min.

WARNING:

Before providing DC power, ensure the voltage and polarity provided are compatible with the DC input. Improper input voltage and/or polarity can be responsible for system damage.
AVERTISSEMENT: Avant de fournir une alimentation CC, assurez-vous que la tension et la polarité fournies sont compatibles avec l'entrée CC. Une tension d'entrée et / ou une polarité incorrectes peuvent être responsables de dommages au système.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.1.14 COM Port Connectors

The MXC-6600 Series provides six COM ports through D-sub 9-pin connectors. The COM1 & COM2 ports support RS-232/422/485 modes by BIOS setting, while COM3 through COM6 support only RS-232.




Figure 3-8: COM Port Pin Definition

Pin	Signal Name		
	RS-232	RS-422	RS-485
1	DCD#	TXD422-	485DATA-
2	RXD	TXD422+	485DATA+
3	TXD	RXD422+	N/S
4	DTR#	RXD422-	N/S
5	GND	N/S	N/S
6	DSR#	N/S	N/S
7	RTS#	N/S	N/S
8	CTS#	N/S	N/S
9	RI#	N/S	N/S

Table 3-11: D-Sub 9-pin Signal Function of COM Ports

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.1.15 CFast Host Slot

The MXC-6600 Series is equipped with a Type II Push-Push CFast host slot on the front panel, by SATA interface. Data transfer rates up to 3.0Gb/s (300MB/s) are supported. The host SATA controller provides a legacy operating mode using I/O space, and an AHCI operating mode using memory space. The CFast card can function as a storage device for system installation.

To install a CFast card, remove the 2 screws securing the cover to the chassis and remove the cover. Install the card and replace the cover using the 2 screws




Figure 3-9: CFast Host Slot

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.2 Internal I/O Connectors

3.2.1 Mainboard Connector Locations




Figure 3-10: Mainboard Connectors

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

A	Fan connector
B	SATA connector1
C	SATA connector2
D	USB 2.0 dongle
E	BP slot
F	BP slot
G	For MXM card power wafer
H	FM board to board connector
I	CFast connector
J	Battery socket
K	DDR4 slot
L	M.2 connector
M	Sim card socket by M.2
N	Sim card socket by Mini PCIe
O	Mini PCIe socket
P	GPS wafer
Q	Speaker wafer
R	DIO and COM port 5 and 6 and audio wafer
S	COM port 3 and 4 wafer
T	I^2C0 wafer
U	Power and Reset wafer
V	I^2C1 wafer
W	4-pin DC_input
X	Clear CMOS connector

Table 3-12: Mainboard Connector Legend

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.2.2 2-slot Backplane Connector Locations

MXC-662X, MXC-6621, MXC6622, MXC-6623



Figure 3-11: 2-slot Backplane Board Connectors

A	USB 2.0 dongle connector
B	SATA power connector
C	SATA signal connector
D	PCI Express x4 slot
E	PCI Express x16 slot
F	Additional power for PCIe x16 slot (12V and 5V)
G	Direct SATA connector

Table 3-13: 2-slot Backplane Board Connector Legend

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.2.3 4-slot Backplane Connector Locations

MXC-664X, MXC-6641, MXC-6642, MXC-6643




Figure 3-12: 4-slot Backplane Board Connectors

A	SATA power
B	SATA signal
C	Additional power for PCIe slot (12V)
D	USB 2.0 dongle
E	Fan
F	Direct SATA
G	PCI slot
H	PCIe x4 slot
I	PCIe x16 slot

Table 3-14: 4-slot Backplane Board Connector Legend

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.2.4 GPS Module Power Headers

Power supply via cable for Mini PCIe GPS module cards (5V).




Figure 3-13: GPS Module Power Header Pin Definition

Pin	Signal
1	+5V_GPS
2	GND

Table 3-15: GPS Module Power Header Pin Definition

3.2.5 USB 2.0 Connector

One USB 2.0 Type-A connector is provided on the mainboard for internal USB dongle, with another on the backplane board.

3.2.6 Mini PCIe Connector

The internal Mini PCIe connector (Rev. 1.2) supports full size Mini PCIe cards.

3.2.7 SATA Connector

The SATA connector supports transfer up to 6.0Gb/s (600MB/s).

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.2.8 12V Fan Connector

DC 12V fan module power supply is provided through the connector, to which the optional fan module connects when installed in the chassis.




Figure 3-14: 12V Fan Connector Pin Definition

Pin	Signal
1	FAN_GND
2	P_+12V_FAN
3	SIO_FAN_IN
4	SIO_FAN_OUT

Table 3-16: 12V Fan Connector Pin Definition

3.2.9 Clear CMOS Jumper

Upon encountering an abnormal condition preventing the MVP-6100 from booting, the jumper can clear the BIOS content stored in CMOS and restore default settings. To clear CMOS, short pin #1 to pin #2 for a minimum of 3 seconds, and then remove the jumper to return to normal mode (replace to pins #2 and #3, default).



Figure 3-15: Clear CMOS Jumper Setting

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

3.2.10 Extended PWR/RESET Header

An internal header is provided for the Power and Reset buttons, with pin definition as shown.




Figure 3-16: PWR/RESET Header Pin Definition

Pin	Signal
1	PWR_BTN-L
2	GND
3	GND
4	RESET_BTN-L

Table 3-17: PWR/RESET Header Pin Definition

3.2.11 USIM Slot

The USIM slot connects to the Mini PCIe and M.2 slots.

3.2.12 12V Power for Additional AFM MXM Carrier Board

One 12V power pin header provides additional AFM MXM carrier board power for an MXM card, if used.




Figure 3-17: 12V Power Pin Definition

Pin	Signal	Pin	Signal
1	P_+12V_B	3	GND
2	P_+12V_B	4	GND

Table 3-18: 12V Power Pin Definition

NOTE:

For additional information regarding the AFM MXM Carrier Board, please contact your ADLINK representative.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

4 Getting Started

4.1 Attach DC Power Connector

Locate the DC power connector shown below that is included in the Accessory Box. Insert it into the DC Power Input “A” shown in **Figure 3-1** on page 15 and secure it to the chassis using the captive screws.



Connect a DC power source as described in **Section 3.1.13: DC Power Input on page 23** to the inputs of the DC power connector, making sure to use the correct input voltage andpolarity.

WARNING:

Before providing DC power, ensure the voltage and polarity provided are compatible with the DC input. Improper input voltage and/or polarity can be responsible for system damage.
AVERTISSEMENT: Avant de connecter à une source de courant continu, veuillez vous assurer de la polarité de la tension conformément à l'entrée CC du PC. Une tension et/ou une polarité incorrectes peuvent causer des dommages irréversibles sur le système.


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

4.2 Mounting the MXC-6600 Series

4.2.1 Install the Wall-mount Brackets

Use the 6 M4 6mm screws included in the Accessory Box to attach the 2 included wall-mount brackets to the chassis as indicated by the red circles below.

Utilisez les 6 vis M4 6 mm incluses dans la boîte d'accessoires pour fixer les 2 supports de montage mural inclus au châssis, comme indiqué par les cercles rouges ci-dessous.




LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Mounting the Device / Montage de l'Appareil

Mount the device to a wall using the 4 keyhole openings indicated or the 6 mounting holes circled in red, according to the spacing dimensions of the holes in the bracket as shown in Figure 2-2 MXC-6620 Front View and Figure 2-3 MXC-6640 Front View.

Montez l'appareil sur un mur à l'aide des 4 ouvertures de trou de serrure en fonction des dimensions d'espacement des trous dans le support, comme indiqué dans Figure 2-2 MXC-6620 Front View et Figure 2-3 MXC-6640 Front View.



LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

4.3 Driver Installation

Download the Windows 10 drivers for your system from the product page at https://www.adlinktech.com/Products/Industrial_PCs_Fanless_Embedded_PCs/IntegratedFanlessEmbeddedComputers/MXC-6600_Series and install.

The following drivers must be installed:

- Chipset
- Graphics
- Audio
- Ethernet
- Intel ME
- DI/O

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Appendix A Power Consumption



Information in this Appendix is for power budget planning and design purposes only. Actual power consumption may differ based on final application.

A.1 Power Consumption Reference

Power consumption as follows is based on lab data in which 24V DC is applied and current is measured by the DC power supply. The power consumption (W) is calculated as the product of applied voltage (V) and the current (A).

Platforms tested for this data have available external I/O interfaces, and are attached to supported devices such as VGA and DVI monitors, CFast card, USB dummy load, COM loopback, and audio loopback, and an internal hard disk driver is installed.

Information is presented for reference only. Actual power consumption will vary with different attached devices and operating system.

System	Power Off	System Idle	Processor Full Load	System Full Load	Recommended Power Supply
MXC-660X Intel® Xeon®	6.8W	23W	78W	118W	220 or 280W
MXC-6601 Intel® Core™ i7	6.7W	23W	78W	117W	220 or 280W
MXC-6602 Intel® Core™ i5	6.8W	23W	77W	117W	220 or 280W
MXC-6603 Intel® Core™ i3	6.8W	22W	55W	93W	220 or 280W

Table A-1: Power Consumption

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



NOTE:

- Sufficient power supply for the entire system is required to meet these specifications. At least 100W at 24V input is recommended.
- Heat generated by add-on PCI/PCIe adapters affects thermal stability. Additional heat dissipation is required when the system operates at high temperatures or in harsh environments with add-on adapters.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Appendix B BIOS Setup

The Basic Input/Output System (BIOS) is a program that provides a basic level of communication between the processor and peripherals. In addition, the BIOS also contains codes for various advanced features applied to the MXC-6600 Series. The BIOS setup program includes menus for configuring settings and enabling features of the MXC-6600 Series. Most users do not need to use the BIOS setup program, as the MXC-6600 Series ships with default settings that work well for most configurations.

Enter BIOS setup by pressing <DEL> when the system is powered on and the POST (power-on self-test) message is displayed. The MXC-6600 Series controller supports one-time Boot Menu allowing selection of the boot device. Enter the Boot Menu by pressing <F7> during POST.


NOTE:

- BIOS options listed are for reference only.
- Different configurations can affect BIOS behavior.
- Displayed material may reflect only the BIOS version corresponding to initial release and may differ from that of the purchased motherboard.
- Users can download the latest BIOS version from the ADLINK website.


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.1 Main

Contains basic system information for the MXC-6600 Series.

WARNING:

Changing BIOS settings may lead to incorrect controller behavior and possible inability to boot. In such a case, Section 3.2.9:Clear CMOS Jumper provides instruction on clearing the CMOS and restoring default settings



BIOS Information

Shows current system BIOS Vendor, BIOS Version, Build Date, MRC Version, GOP Version and ME FW Version.

System Information

Shows current system Project Name, CPU Board Version, CPU Branding String, CPU Stepping, GT Info, CPU Frequency, Total Memory, Memory Frequency, PCH SKU and Stepping.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

System Time/System Date


Allows adjustment of system time and date, as follows.

1. Highlight System Time or System Date using the up and down <Arrow> keys
2. Enter new values using the keyboard and select <Enter>
3. Select < Tab > to move between fields.

NOTE:

- The date must be entered in MM/DD/YY format, and the time in HH:MM:SS.
- The time is in 24-hour format. For example, 5:30 A.M. appears as 05:30:00, and 5:30 P.M. as 17:30:00.

B.2 Advanced




CAUTION:


Setting incorrect or conflicting values in Advanced BIOS Setup may cause a system malfunction

Accesses advanced options of the MXC-6600 Series.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.1CPU Configuration





LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Hyper-Threading

Enabled for Windows 7, 10 IoT Enterprise, and Linux (optimized for Hyper-Threading Technology). When Disabled only one thread per enabled core is enabled.

Active Processor Cores

Number of cores to enable in each processor package.

Intel (VMX) Virtualization Technology

When enabled, a VMM can utilize the additional hardware capabilities provided by Vanderpool Technology.

Intel Trusted Execution Technology

Enables/Disables Intel TXT feature.

Intel(R) SpeedStep(tm)

Allows more than two frequency ranges to be supported.

Intel(R) Speed Shift Technology

Enables/Disables Intel(R) Speed Shift Technology support. Enabling will expose the CPPC v2 interface to allow for hardware controlled P-states.

C States


Enables/Disables CPU Power Management. Allows CPU to go to C states when it is not 100% utilized.

TCC Activation Offset

Offset from factory set Tcc activation temprature at which the Thermal Control Circuit must be activated. Tcc will be activated at: Tcc Activation Temp - Tcc Activation Offset. The Tcc Activation Offset range is 0 to 63.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.2 Power Management



State After G3

Specify what state to go to when power is re-applied after a power failure (G3 state).

RTC Wake system from S5


Enables/Disables the system wake on alarm event. Select Fixed-Time, and the system will wake on the hr::min::sec specified. Select DynamicTime, the system will wake on the current time + Increase minute(s).

Ring Wake

Enables/Disables RI ping for Wake On Ring function (PCH PME# signal).

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.3 Serial Console Configuration



COM1

Console Redirection

Enables/Disables SIO COM1 Console Redirection.

Console Redirection Settings

The settings specify how the host computer and the remote computer (which the user is using) will exchange data. Both computers should have the same or compatible settings.

COM2

Console Redirection

Enables/Disables SIO COM2 Console Redirection.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Console Redirection Settings

The settings specify how the host computer and the remote computer (which the user is using) will exchange data. Both computers should have the same or compatible settings.

COM SOL (Pci Bus0, Dev22.Fun3)

Console Redirection


Enables/Disables AMT PCI SOL Console Redirection.

Console Redirection Settings

The settings specify how the host computer and the remote computer (which the user is using) will exchange data. Both computers should have the same or compatible settings.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.4 USB Configuration



USB Mass Storage Driver Support

Enables/Disables USB mass storage driver support.

USB transfer time-out

Timeout value for Control, Bulk, and Interrupt transfers.

Device reset time-out

USB mass storage device Start Unit command timeout.

Device power-up delay

Maximum time taken before the device reports itself to the Host Controller, with Auto using a default value of 100 ms for a Root port, and for a Hub port the delay is taken from the Hub descriptor.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.5 TPM 2.0 Configuration



Security Device Support

Enables/Disables BIOS support for security devices. The operating system will not show the security device. The TCG EFI protocol and INT1A interface will not be available.

SHA-1 PCR Bank

Enables/Disables SHA-1 PCR Bank.

SHA256 PCR Bank

Enables/Disables SHA256 PCR Bank.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Pending operation

Schedule an operation for the security device.



The computer will reboot in order to change the state of the security device.

Platform Hierarchy

Enables/Disables Platform Hierarchy.

Storage Hierarchy

Enables/Disables Storage Hierarchy.

Endorsement Hierarchy

Enables/Disables Endorsement Hierarchy.

TPM2.0 UEFI Spec Version

Select the TCG2 specification support version.

Physical Presence Spec Version

Select to specify support for PPI specification version 1.2 or 1.3.




Some HCK tests might not support version 1.3.

Device Select

TPM 1.2 will restrict support to TPM 1.2 devices, TPM 2.0 will restrict support to TPM 2.0 devices, Auto will support both with the default set to TPM 2.0 devices if not found, and TPM 1.2 devices will be enumerated.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.6 AMT Configuration



AMT BIOS Features


When disabled, AMT BIOS Features are no longer supported and the user is no longer able to access MEBx Setup.

MEBx hotkey Pressed

Enable automatic MEBx hotkey press.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.7 Onboard Devices Configuration



COM1 Control

Sets port type (RS-232/422/485) for COM1 serial port.

COM2 Control

Sets port type (RS-232/422/485) for COM2 serial port.

LAN #1 (Intel I219)


Enables/Disables onboard Intel I219 LAN controller.

LAN #2 (Intel I211AT)

Enables/Disables onboard Intel I211AT LAN controller.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.8 NCT6106D HW Monitor



NCT6106D HW Monitor

Displays CPU/board temperatures, system fan speed and various voltages.

System Fan Control Mode

Sets the system fan control mode.

T1

T1 (Temperature 1), Range: 1-100

T1 Duty

Set T1 related DC/PWM value, Range: 0-255

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

T2

T2 (Temperature 2), Range: 1-100

T2 Duty

Set T2 related DC/PWM value, Range: 0-255

T3

T3 (Temperature 3), Range: 1-100

T3 Duty

Set T3 related DC/PWM value, Range: 0-255

T4

T4 (Temperature 4), Range: 1-100

T4 Duty

Set T4 related DC/PWM value, Range: 0-255

BP Fan Control Mode

Sets the BP fan control mode.

T1

T1 (Temperature 1), Range: 1-100

T1 Duty

Set T1 related DC/PWM value, Range: 0-255

T2

T2 (Temperature 2), Range: 1-100

T2 Duty

Set T2 related DC/PWM value, Range: 0-255

T3

T3 (Temperature 3), Range: 1-100

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

T3 Duty

Set T3 related DC/PWM value, Range: 0-255

T4


T4 (Temperature 4), Range: 1-100

T4 Duty

Set T4 related DC/PWM value, Range: 0-255

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.2.9 BIOS Watchdog Timer



BIOS POST Watchdog


Disable: Disables watchdog timer.

Second Mode: Enables watchdog timer in seconds mode.

Minute Mode: Enables watchdog timer in minutes mode.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3 Chipset




CAUTION:

Setting incorrect or conflicting values in Chipset BIOS Setup may cause a system malfunction.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.1 System Agent (SA) Configuration




System Agent (SA) Configuration

Display and configure VT-d's capability and provide settings for memory, graphics and DMI/OPI configuration.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.1.1 Memory Configuration




Memory Configuration

Display memory speed, size, brand and configuration.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.1.2 Graphics Configuration



Primary Display

Selects which of the IGFX/PEG/PCH PCI(e) graphics devices should be the primary display. Select SG for Switchable Gfx.

Internal Graphics

Keep IGFX enabled based on the Setup options.

GTT Size

Sets GTT size.

Aperture Size

Sets aperture size.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


DVMT Pre-Allocated

Sets size of DVMT 5.0 pre-allocated (fixed) graphics memory used by the internal graphics device.

DVMT Total Gfx Mem

Sets size of DVMT5.0 total graphic memory used by the internal graphics device.

B.3.1.3 DMI/OPI Configuration



DMI/OPI Configuration


Display DMI link speed and width.

DMI Max Link Speed

Set sDMI speed to Gen1/Gen2/Gen3.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.2 PCH-IO Configuration




PCH-IO Configuration

Provides for SATA, Security and HD Audio configuration.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.2.1 SATA And RST Configuration



SATA Mode Selection

Determines how SATA controller(s) operate.

SATA Controller Speed

Sets the maximum speed the SATA controller can support.

M.2 Storage

Enables/Disables M.2 storage.

CFast Card

Enables/Disables CFast card.

Hot Plug

Designates selected port as hot pluggable.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

SATA HDD 1

Enables/Disables SATA HDD 1

SATA HDD 2

Enables/Disables SATA HDD 2

SATA HDD 3


Enables/Disables SATA HDD 4

SATA HDD 4

Enables/Disables SATA HDD 4

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.2.2 Security Configuration




BIOS Lock

Enable/Disable the PCH BIOS Lock Enable feature. Required to be enabled to ensure SMM protection of flash.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.2.3 HD Audio Configuration




Audio Output Selection

Selects the audio output device.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.3.2.4 BackPlane PCIe Configuration



BackPlane PCIe Configuration


Displays the BackPlane type, link speed and width.

Speed

Controls the PCIe maximum speed.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.4 Security



If only the Administrator password is set, access s limited and the password requested on Setup. If User password is set, it acts as a power-on password and must be entered to boot or enter setup. In Setup the user receives

Administrator Password


Sets Administrator Password.

User Password

Sets User Password.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.4.1 Secure Boot Menu




Secure Boot Control

The Secure Boot feature is Active if Secure Boot is enabled, Platform Key (PK) is enrolled and the system is in User mode. Changing the system mode requires a platform reset.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.5 Boot



Setup Prompt Timeout

Number of seconds before setup activation key is launched, with 65535(0xFFFF) setting an indefinite wait time.

Bootup Num-Lock State

Sets keypad Number Lock status following boot.

Quiet Boot

Option	Description
Disabled	Directs BIOS to display POST messages
Enabled	Directs BIOS to display the OEM logo.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Fast Boot

Option	Description
Disabled	Directs BIOS to perform all POST tests.
Enabled	Directs BIOS to skip certain POST tests to boot faster.

While enabling Fast Boot can reduce system ready time, some prerequisites can reduce effectiveness

Boot mode select

Sets legacy or UEFI boot mode.

Boot Configuration


Specifies the priority of boot devices, all of which are detected during POST and displayed. Target Boot Option # and click to select the desired device.

UEFI USB Hard Drive Disk Drives BBS Priorities

Specifies the Boot Device Priority sequence from available UEFI USB drives.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

B.6 Save & Exit



Save Changes and Exit

Saves all changes before exiting Setup.

Discard Changes and Exit

Discards all changes and exits Setup.

Save Changes and Reset

Saves all changes and reboots the system with the new settings.

Discard Changes and Reset

Discards all changes and reboots the system.

Save Changes

Saves all changes without exiting Setup.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Discard Changes

Discards all changes without exiting Setup.

Restore Defaults

Sets all BIOS options to default settings, designed for maximum system stability but less than maximum performance. Select Restore Defaults if the computer encounters system configuration problems.

Save as User Defaults

Save the current changes as user defaults.

Restore User Defaults

Restores user defaults to all Setup options.

Launch EFI Shell from filesystem device

Attempts to launch EFI Shell application (Shell.efi) from one of the available filesystem devices.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Appendix C Watchdog Timer (WDT) Function Library

This appendix describes use of the watchdog timer (WDT) function library for the MXC-6600 Series controller. The watchdog timer is a hardware mechanism provided to reset the system if the operating system or an application stalls. After starting, the watchdog timer in the application must be periodically reset before the timer expires. Once the watchdog timer expires, a hardware-generated signal is sent to reset the system.

C.1 WDT with API/Windows

The WDT API library files and a demo program (incl. source code) can be downloaded from: https://www.adlinktech.com/Products/Industrial_PCs_Fanless_Embedded_PCs/IntegratedFanlessEmbeddedComputers/MXC-6600_Series

To use the WDT function library for the MXC-6600 Series, include the header file WDT.h and linkage library WDT.lib in the C++ project.

InitWDT

Initializes the watchdog timer function. Must be called before the invocation of any other WDT function.

Syntax

C/C++

```
BOOL InitWDT()
```

Parameters

None

Return codes

TRUE if watchdog timer is successfully initialized.

FALSE if watchdog timer fails to initialize.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

SetWDT

Sets the timeout value of the watchdog timer. There are two parameters for this function to indicate the timeout ticks and unit. ResetWDT or StopWDT should be called before the expiration of watchdog timer, or the system will reset.

Syntax

C/C++

```
BOOL SetWDT(BYTE tick, BYTE unit)
```

Parameters

`tick`

Specify the number of ticks for watchdog timer. A valid value is 1 - 255.

`unit`

Specifies the timeout ticks of the watchdog timer.

Value	Description
0	The unit for one tick is one second. For example, when one tick is specified as 100 and the unit as 0, the timeout value is 100 seconds.
1	The unit for one tick is one minute. For example, whenone tick is specified as 100 and the unit as 1, the timeout value is 100 minutes.

Return codes

TRUE if timeout value of watchdog timer is successfully set.

FALSE if timeout value of watchdog timer is failed to set.

StartWDT

Start the watchdog timer function. Once the StartWDT is invoked, the watchdog timer starts. ResetWDT or StopWDT should be called before the expiration of watchdog timer, or the system will reset.

Syntax

C/C++

```
BOOL StartWDT()
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Parameters

None

Return codes

TRUE if watchdog timer is successfully started.

FALSE if watchdog timer is failed to start.

ResetWDT

Reset the watchdog timer. The invocation of ResetWDT allows restoration of the watchdog timer to the initial timeout value specified in SetWDT function. ResetWDT or StopWDT should be called before the expiration of the watchdog timer, or the system will reset.

Syntax

C/C++

```
BOOL ResetWDT()
```

Parameters

None

Return codes

TRUE if watchdog timer is successfully reset.

FALSE if watchdog timer fails to reset.

StopWDT

Stops the watchdog timer.

Syntax

C/C++

```
BOOL StopWDT()
```

Parameters

None

Return codes

TRUE if watchdog timer is successfully stopped.

FALSE if watchdog timer fails to stop.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

C.2 WDT with DOS/Linux

Under Linux, please program the WDT function using the LPC IO registers according to the sample program as follows.

```
#include <dos.h>
#include <stddef.h>
#include <stdio.h>
/* Config LPC IO NCT6102D to enter config mode */
EnterConfig(void)
{
outp(0x4E, 0x87);
outp(0x4E, 0x87);
}
/* Config LPC IO to exit config mode */
ExitConfig(void)
{ outp(0x4E, 0xAA);
 }
/* Read byte from LPC IO register */
unsigned char r_reg(unsigned char regoffset)
{ outp(0x4E, regoffset);
return inp(0x4F); }
/* Write byte to LPC IO register */
void w_reg(unsigned char regoffset, unsigned char
data)
{ outp(0x4E, regoffset); outp(0x4F, data);
}
main(void)
{
unsigned int    count;
/* print program title  */
printf("-----------------MXC-6400 WDT Demo-----------
-----\n");
printf("Init and config GPIO
ports<<<<<<<<<<<<<<<<<<<<<<<<\n");
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

```
printf("-----------------------------------------------
----\n");
EnterConfig();
/* config WDT registers */
w_reg(0x07,0x08);
/* enable keyboard interrupt to reset WDT timeout
value */
w_reg(0xF2,r_reg(0xF2)|0x40);
/* set unit as second */
w_reg(0xF0,r_reg(0xF0)&~0x04);
/* start the Watchdog */
w_reg(0x30,0x01);
/* set timeout value as 30 seconds */
/* WDT start automatically while timeout value is set
*/
w_reg(0xF1,0x1E);


printf("-----------------------------------------------
-----\n");
printf("WDT is set and counting down
now.<<<<<<<<<<<<<<<<<\n");
printf("-----------------------------------------------
-----\n");
for(count=30;count!=0;count--)
{ printf("Countdown %2d :  .\n",count);
/* reset WDT timeout value to 10 seconds */
/* w_reg(0x73,0x0A); */
sleep(1);
}
/* disable WDT */
/* WDT stop while timeout value is set to zero */
w_reg(0x30,0x00);
printf("WDT is disable. Program is terminating.");
ExitConfig();
return 0;
}
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

This page intentionally left blank.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Appendix D Digital Input/Output Function Library

DI/O provides input/output to support inter-device communications. Simple programming guides allow easy transmission of digital signals between the system and attached peripherals.

DI/O with API/Windows

Matrix DI/O API library files and a demo program (including source code) can be downloaded from http://www.adlinktech.com.

To use the DI/O function library for the MXC-6600 Series, include the header file matrix_dio.h and linkage library matrix_dio.lib (matrix_dio64.lib for x64 operating systems) in the C++ project.

Error Macro Definition

NoError	0
ErrorOpenDriverFailed	-13
ErrorDeviceIoctl	-200

DI/DO Macro Definition

DI0	DO0	0x01
DI1	DO1	0x02
DI2	DO2	0x04
DI3	DO3	0x08
DI4	DO4	0x10
DI5	DO5	0x20
DI6	DO6	0x40
DI7	DO7	0x80

LED Macro Definition

LED0	0x01
LED1	0x02
LED2	0x04
LED3	0x08
LED4	0x10

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

DI/O Functions

ADMX_DIO_Init

Initializes the DI/O function library.

Syntax

C/C++

```
short __stdcall ADMX_DIO_Init ()
```

Parameter(s)

N/A

Return codes

```
     0: NoError
   -13: ErrorOpenDriverFailed
  -200: ErrorDeviceIoctl
```

ADMX_DIO_Close

Closes the DI/O function library.

Syntax

C/C++

```
short __stdcall ADMX_DIO_Close ()
```

Parameter(s)

N/A

Return codes

```
     0: NoError
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

ADMX_DI_ReadPort

Reads the digital logic state of a digital input line.

Syntax

C/C++

```
short __stdcall ADMX_DI_ReadPort(unsigned long*
     pwState)
```

Parameter(s)

pwState

The state values of MXC-6600 Series digital input channels 1 to 8 (corresponding values 0 to 7)

```
1: Corresponding input/output line is HIGH
0: Corresponding input/output line is LOW
```

Return codes

```
  0: NoError
-13: ErrorOpenDriverFailed
-200: ErrorDeviceIoctl
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

ADMX_DO_WritePort

Sets the digital logic state of a digital output line.

Syntax

C/C++

```
short __stdcall ADMX_DO_WritePort(unsigned long
     wState)
```

Parameter(s)

wState

Sets the state values of MXC-6600 Series digital output channels 1 to 8 (corresponding values 0 to 7)

```
1: Corresponding input/output line is HIGH
0: Corresponding input/output line is LOW
```

Return codes

```
  0: NoError
-13: ErrorOpenDriverFailed
-200: ErrorDeviceIoctl
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

ADMX_DO_ReadPort

Reads the digital logic state of a digital output line.

Syntax

C/C++

```
short __stdcall ADMX_DO_ReadPort(unsigned long*
     pwState)
```

Parameter(s)

pwState

The state values of MXC-6600 Series digital output channels 1 to 8 (corresponding values 0 to 7)

```
1: Corresponding input/output line is HIGH
0: Corresponding input/output line is LOW
```

Return codes

```
  0: NoError
-13: ErrorOpenDriverFailed
-200: ErrorDeviceIoctl
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

LED_Write

Sets the LED digital logic state of the MXC-6600 Series.

Syntax

C/C++

```
short __stdcall LED_Write(unsigned short wState)
```

Parameter(s)

wState

Sets the state values of MXC-6600 Series LED channels 1 to 5 (corresponding values 0 to 4)

```
1: Corresponding input/output line is HIGH
0: Corresponding input/output line is LOW
```

Return codes

```
  0: NoError
-13: ErrorOpenDriverFailed
-200: ErrorDeviceIoctl
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

LED_Read

Reads the LED digital logic state of the MXC-6600 Series.

Syntax

C/C++

```
short __stdcall LED_Read(unsigned short wState)
```

Parameter(s)

wState

The state values of MXC-6600 Series LED channels 1 to 5 (corresponding values 0 to 4)

```
1: Corresponding input/output line is HIGH
0: Corresponding input/output line is LOW
```

Return codes

```
   0: NoError
 -13: ErrorOpenDriverFailed
-200: ErrorDeviceIoctl
```


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

This page intentionally left blank.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Important Safety Instructions

For user safety, please read and follow all instructions, Warnings, Cautions, and Notes marked in this manual and on the associated device before handling/operating the device, to avoid injury or damage.

- Read these safety instructions carefully.
- Keep the User's Manual for future reference.
- Read the Specifications section of this manual for detailed information on the recommended operating environment.
- The device can be operated at an ambient temperature of 50ºC with DC input, and 35ºC with adapter input.
- It is recommended that the device be installed in Information Technology Rooms that are in accordance with Article 645 of the National Electrical Code and NFPA 75.
- To avoid electrical shock and/or damage to device:
  - Keep device away from water or liquid sources.
  - Keep device away from high heat or humidity.
  - Keep device properly ventilated (do not block or cover ventilation openings).
  - Always use recommended voltage and power source settings.
  - Always install and operate device near an easily accessible electrical outlet.
  - Secure the power cord (do not place any object on/over the power cord).
  - Only install/attach and operate device on stable surfaces and/or recommended mountings.
  - The power cord must be connected to a socket or outlet with a ground connection.
- If the device will not be used for long periods of time, turn off and unplug from its power source.
- Never attempt to repair the device, which should only be serviced by qualified technical personnel using suitable tools.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

- A Lithium-type battery may be provided for uninterrupted backup or emergency power.



Risk of explosion if battery is replaced with one of an incorrect type; please dispose of used batteries appropriately.

- This equipment is not suitable for use in locations where children are likely to be present.
- The device must be serviced by authorized technicians when:
  - The power cord or plug is damaged
  - Liquid has entered the device interior
  - The device has been exposed to high humidity and/or moisture
  - The device is not functioning or does not function according to the User's Manual
  - The device has been dropped and/or damaged and/or shows obvious signs of breakage
- Disconnect the power supply cord before loosening the thumbscrews and always fasten the thumbscrews with a screwdriver before starting the system up
- It is recommended that the device be installed only in a server room or computer room where access is:
  - Restricted to qualified service personnel or users familiar with restrictions applied to the location, reasons therefor, and any precautions required
  - Only afforded by the use of a tool or lock and key, or other means of security, and controlled by the authority responsible for the location



BURN HAZARD

Hot surface! Do not touch! Touching this surface could result in bodily injury. To reduce risk, allow the surface to cool before touching.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Consignes de Sécurité Importante

S'il vous plaît prêter attention stricte à tous les avertissements et mises en garde figurant sur l'appareil, pour éviter des blessures ou des dommages.

- *Lisez attentivement ces consignes de sécurité.*
- *Conservez le manuel de l'utilisateur pour pouvoir le consulter ultérieurement.*
- *Lisez la section Spécifications de ce manuel pour des informations détaillées sur l'environnement d'exploitation recommandé.*
- *L'appareil peut être utilisé à une température ambiante de 50°C avec entrée CC; 35ºC avec entrée adaptateur.*
- *Il est recommandé d'installer l'appareil dans des salles de technologie de l'information conformes à l'article 645 du National Electrical Code et à la NFPA 75.*
- *Pour éviter les chocs électriques et/ou d'endommager l'appareil:*
  - *Tenez l'appareil à l'écart de toute source d'eau ou de liquide.*
  - *Tenez l'appareil à l'écart d'une forte chaleur ou d'une humidité élevée.*
  - *Maintenez l'appareil correctement ventilé (n'obstruer ou ne couvrez pas les ouvertures de ventilation).*
  - *Utilisez toujours les réglages de tension et de source d'alimentation recommandés.*
  - *Installez et utilisez toujours l'appareil près d'une prise de courant facilement accessible.*
  - *Fixez le cordon d'alimentation (ne placez aucun objet sur le cordon d'alimentation).*
  - *Installez/fixez et utilisez l'appareil uniquement sur des surfaces stables et/ou sur les fixations recommandées.*
  - *Le cordon d'alimentation doit être connecté à une prise ou à une prise de courant avec mise à la terre.*

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

- Si l'appareil ne doit pas être utilisé pendant de longues périodes, éteignez-le et débranchez-le de sa source d'alimentation
- *N'essayez jamais de réparer l'appareil, qui ne doit être réparé que par un personnel technique qualifié à l'aide d'outils appropriés*
- *Une batterie de type Lithium peut être fournie pour une alimentation de secours ininterrompue ou d'urgence.*



ATTENTION: Risque d'explosion si la pile est remplacée par une autre de type incorrect. Veuillez jeter les piles usagées de façon appropriée.

- *Cet équipement ne convient pas à une utilisation dans des lieux pouvant accueillir des enfants.*
- *L'appareil doit être entretenu par des techniciens agrees lorsque:*
- *Le cordon d'alimentation ou la prise est endommagé(e)*
- *Un liquide a pénétré à l'intérieur de l'appareil.*
- *L'appareil a été exposé à une forte humidité et/ou de la buée.*
- *L'appareil ne fonctionne pas ou ne fonctionne pas selon le manuel de l'utilisateur.*
- *L'appareil est tombé et/ou a été endommagé et/ou présente des signes évidents de dommage.*
- *Débranchez le cordon d'alimentation avant de desserrer les vis à oreilles et serrez toujours les vis à oreilles avec un tournevis avant de mettre le système en marche.*
- *Il est recommandé d'installer l'appareil uniquement dans une salle de serveurs ou une salle informatique où l'accès est:*
  - *Réservé au personnel de service qualifié ou aux utilisateurs familiarisés avec les restrictions appliquées à l'emplacement, aux raisons de ces restrictions et toutes les précautions requises*
  - *Uniquement autorisé par l'utilisation d'un outil, d'une serrure et d'une clé, ou d'un autre moyen de sécurité, et contrôlé par l'autorité responsable de l'emplacement.*

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

	***RISQUE DE BRÛLURES*** ***Partie chaude!*** *Ne touchez pas cette surface, cela pourrait entraîner des blessures. Pour éviter tout danger, laissez la surface refroidir avant de la toucher.*

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

This page intentionally left blank.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Getting Service

Ask an Expert: http://askanexpert.adlinktech.com

ADLINK Technology, Inc.
9F, No.166 Jian Yi Road, Zhonghe District
New Taipei City 235, Taiwan
Tel: +886-2-8226-5877
Fax: +886-2-8226-5717
Email: service@adlinktech.com

Ampro ADLINK Technology, Inc.
5215 Hellyer Avenue, #110
San Jose, CA 95138, USA
Tel: +1-408-360-0200
Toll Free: +1-800-966-5200 (USA only)
Fax: +1-408-360-0222
Email: info@adlinktech.com

ADLINK Technology (China) Co., Ltd.
300 Fang Chun Rd., Zhangjiang Hi-Tech Park
Pudong New Area, Shanghai, 201203 China
Tel: +86-21-5132-8988
Fax: +86-21-5132-3588
Email: market@adlinktech.com

ADLINK Technology GmbH
Hans-Thoma-Straße 11
D-68163 Mannheim, Germany
Tel: +49-621-43214-0
Fax: +49-621 43214-30
Email: emea@adlinktech.com

Please visit the Contact page at www.adlinktech.com for information on how to contact the ADLINK regional office nearest you:

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000