
ADLINK
LEADING EDGE AI COMPUTING

SBC35-ASL

3.5" Single Board Computer with Intel® x7835RE/x7433RE/x7211RE Processor

Features

- Intel® x7835RE/x7433RE/x7211RE Processor
- DDR5 4800MHz memory up to 16GB
- Three independent display: eDP/LVDS HDMI, DP
- Dual GbE ports: 1GbE (Intel i210IT)
- SBC-FM board expansion: PCIe x1, USB2.0, LPC
- TPM 2.0 (option)
- Wide operating temperature range: -40°C to 85°C



Windows Ubuntu Certified ASD+ 85°C -40°C

Ordering Information

PN	Model Name	CPU	Memory	DP	HDMI	LCD	COM	SATA	USB2.0	USB3.0	M.2	SBC-FM	TPM
91-44840-60XX	SBC35-ASL	X7433RE	DDR5 SO-DIMM 4800 MHz	1	1	LVDS	4	1	3	1	3	Support	Support (option)

* others skus request MOQ, please contact with your sales.

Packing Lists

PN	Description	QTY
91-44840-60XX	SBC35-ASL	1
58-10515-0000	M.2 screw kit	1

Optional Accessories

PN	Description
32-21039-0000-A0	Passive Heatsink
30-21534-0010-A0	RS-232x2+ RS-232/RS-485/RS-422x2
30-21611-0000-A0	RS-232x2
30-22122-0000-A0	DI/DOx8-bits +Audio +USB 2.0x2
30-22121-0000-A0	SATA + SATA power cable

Embedded OS

PN	Description
92-56094-0010	Windows 10 IoT Ent LTSC 2021 High End PKEA
92-56094-2010	Windows 10 IoT Ent LTSC 2021 Value PKEA
92-56094-4010	Windows 10 IoT Ent LTSC 2021 Entry PKEA
92-56101-0010	Windows 11 IoT Ent 2022 High End PKEA
92-56101-2010	Windows 11 IoT Ent 2022 Value PKEA
92-56101-4010	Windows 11 IoT Ent 2022 Entry PKEA


LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Specifications


Model	SBC35-ASL
Processor System	
CPU	X7433RE, 4 cores, 3.4GHz, 9W
Memory	1x DDR5 SO-DIMMs, up to 4800MHz, up to 16GB
Operating Systems	Windows 10/11 (64-bit) Ubuntu 22.04 (Support by project)
Display	
VGA	-
LVDS/ eDP	eDP/ LVDS*1 (default LVDS)
HDMI	1
DisplayPort	1
Number of Displays Supported	3
Ethernet	
Gbe Port	2
Controller/ Frequency	2x Intel® i210IT, support 1Gbps/ 100Mbps / 10Mbps
I/O Interfaces	
USB	1x USB 3.2 Gen 2x1 ports (10Gbps) (rear I/O) 3x USB 2.0 (rear I/O)
COM	COM1: RS-232/422/485 (rear I/O) COM2: RS-232/422/485 DB9 or 40pin box header (default) by BOM option COM3/4: 2x RS-232 through 40pin box header
Serial ATA	1x SATA 6Gb/s ports w/ 5V SATA power
Audio	Realtek ALC888S 1x line-in, 1x line-out, MIC-in through 40pin box header
Expansion Slots	M.2 2280 M Key (PCIex2) M.2 2230 E Key with (Wi-Fi(PCIex1), BT(USB2.0)) M.2 3042 B-key (USB3.0/2.0) w/ SIM card
TPM	Yes (TPM 2.0, option)
DI/ DO	8 DI and 8 DO through 40pin box header
SBC-FM board expansion	
PCIex1	1
PCIe x4	-
USB3.0/2.0	USB2.0 x1
LPC	Yes
Mechanical and Environment	
Form Factor	3.5" Single Board Computer
Dimension	5.75" x 4" (146mm x 102mm)
Power Supply	12V-24V Reserve DC JACK connector (option)
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Certification	
EMC	CE & FCC Class B
ESD	Contact +/-4 KV, Air +/-8 KV

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Product Illustration



Block Diagram



* co-lay by BOM change, please contact with your local sales.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

CPU Support List

Family	Number	CPU Core	Frequency	Processor Base Power
Intel Atom® Processor X Series	x7433RE	4 Core	3.4GHz	9W
	x7211RE	2 Core	3.2GHz	6W
	x7213RE	2 Core	3.4GHz	6W
	x7835RE	8 Core	3.6GHz	12W

*For the non-standard skus, we support by project based. Please contact with local sales in detail.

All products and company names listed are trademarks or trade names of their respective companies. Updated Mar. 31, 2026. ©2026 ADLINK Technology, Inc. All Rights Reserved. All pricing and specifications are subject to change without further notice.